

SELECTION TABLES
End Suction Fire Pumps
50Hz Electric Motor Driven

Section 911.5 Page 501
 Date November 15, 2018
 Supersedes January 1, 2018

| Flow | Pressure | | Required Motor HP Rating | | | Maximum Shutoff (PSI)* | Pump Model |
|-------------------|----------|------|--------------------------|-------------|------------------|------------------------|------------|
| | PSI | Feet | Motor HP | Speed (RPM) | Horsepower (BHP) | | |
| 50 GPM | 98 | 226 | 30 | 2950 | 31 | 99 | 2-384-11 |
| | 100 | 231 | 30 | 2950 | 32 | 101 | 2-384-11 |
| | 105 | 243 | 30 | 2950 | 33 | 106 | 2-384-11 |
| | 110 | 254 | 40 | 2950 | 35 | 111 | 2-384-11 |
| | 115 | 266 | 40 | 2950 | 37 | 117 | 2-384-11 |
| | 120 | 277 | 40 | 2950 | 39 | 122 | 2-384-11 |
| | 125 | 289 | 40 | 2950 | 41 | 127 | 2-384-11 |
| | 130 | 300 | 40 | 2950 | 44 | 132 | 2-384-11 |
| | 135 | 312 | 40 | 2950 | 46 | 137 | 2-384-11 |
| | 140 | 323 | 50 | 2950 | 48 | 143 | 2-384-11 |
| | 145 | 335 | 50 | 2950 | 50 | 148 | 2-384-11 |
| | 150 | 347 | 50 | 2950 | 51 | 153 | 2-384-11 |
| 151 | 349 | 50 | 2950 | 51 | 154 | 2-384-11 | |

| | | | | | | | |
|--------------------|-----|-----|------|------|------|----------|-----------|
| 100 GPM | 43 | 99 | 10 | 2950 | 9.4 | 44 | 2.5-384-7 |
| | 45 | 104 | 10 | 2950 | 10 | 46 | 2.5-384-7 |
| | 50 | 116 | 10 | 2950 | 11.5 | 51 | 2.5-384-7 |
| | 55 | 127 | 15 | 2950 | 14 | 56 | 2.5-384-7 |
| | 59 | 136 | 15 | 2950 | 15 | 60 | 2.5-384-7 |
| | 98 | 226 | 30 | 2950 | 31 | 99 | 2-384-11 |
| | 100 | 231 | 30 | 2950 | 32 | 101 | 2-384-11 |
| | 105 | 243 | 30 | 2950 | 34 | 106 | 2-384-11 |
| | 110 | 254 | 40 | 2950 | 36 | 112 | 2-384-11 |
| | 115 | 266 | 40 | 2950 | 38 | 117 | 2-384-11 |
| | 120 | 277 | 40 | 2950 | 40 | 122 | 2-384-11 |
| | 125 | 289 | 40 | 2950 | 42 | 127 | 2-384-11 |
| | 130 | 300 | 40 | 2950 | 44 | 133 | 2-384-11 |
| | 135 | 312 | 40 | 2950 | 46 | 138 | 2-384-11 |
| | 140 | 323 | 50 | 2950 | 48 | 143 | 2-384-11 |
| | 145 | 335 | 50 | 2950 | 50 | 149 | 2-384-11 |
| 149 | 345 | 50 | 2950 | 51 | 153 | 2-384-11 | |
| 150 | 347 | 50 | 2950 | 51 | 154 | 2-384-11 | |
| 151 | 349 | 50 | 2950 | 52 | 155 | 2-384-11 | |

| | | | | | | | |
|--------------------|-----|-----|------|------|------|----------|-----------|
| 150 GPM | 42 | 97 | 10 | 2950 | 9.4 | 44 | 2.5-384-7 |
| | 45 | 104 | 10 | 2950 | 10.2 | 47 | 2.5-384-7 |
| | 50 | 116 | 15 | 2950 | 12 | 52 | 2.5-384-7 |
| | 55 | 127 | 15 | 2950 | 14 | 57 | 2.5-384-7 |
| | 58 | 135 | 15 | 2950 | 15 | 60 | 2.5-384-7 |
| | 59 | 136 | 15 | 2950 | 15 | 61 | 2.5-384-7 |
| | 97 | 224 | 30 | 2950 | 31 | 99 | 2-384-11 |
| | 100 | 231 | 30 | 2950 | 32 | 102 | 2-384-11 |
| | 105 | 243 | 30 | 2950 | 34 | 108 | 2-384-11 |
| | 110 | 254 | 40 | 2950 | 36 | 113 | 2-384-11 |
| | 115 | 266 | 40 | 2950 | 38 | 118 | 2-384-11 |
| | 120 | 277 | 40 | 2950 | 40 | 123 | 2-384-11 |
| | 125 | 289 | 40 | 2950 | 42 | 128 | 2-384-11 |
| | 130 | 300 | 40 | 2950 | 44 | 134 | 2-384-11 |
| | 135 | 312 | 40 | 2950 | 46 | 139 | 2-384-11 |
| | 140 | 323 | 50 | 2950 | 48 | 144 | 2-384-11 |
| 145 | 335 | 50 | 2950 | 51 | 149 | 2-384-11 | |
| 149 | 343 | 50 | 2950 | 51 | 153 | 2-384-11 | |
| 150 | 347 | 50 | 2950 | 51 | 154 | 2-384-11 | |

*Maximum shutoff includes Hydraulic Institute's tolerance of 6%. Value is used to determine flange rating for the pump.



SELECTION TABLES
End Suction Fire Pumps
50Hz Electric Motor Driven

Section 911.5 Page 502
 Date November 15, 2018
 Supersedes January 1, 2018

| Flow | Pressure | | Required Motor HP Rating | | | Maximum Shutoff (PSI)* | Pump Model |
|----------------|----------|------|--------------------------|-------------|------------------|------------------------|------------|
| | PSI | Feet | Motor HP | Speed (RPM) | Horsepower (BHP) | | |
| 200 GPM | 40 | 92 | 10 | 2950 | 9.2 | 44 | 2.5-384-7 |
| | 44 | 102 | 20 | 2950 | 21 | 45 | 4-384-7 |
| | 45 | 104 | 10 | 2950 | 10.7 | 48 | 2.5-384-7 |
| | | | 20 | 2950 | 21 | 46 | 4-384-7 |
| | 50 | 116 | 15 | 2950 | 13 | 53 | 2.5-384-7 |
| | | | 25 | 2950 | 25 | 52 | 4-384-7 |
| | 55 | 127 | 15 | 2950 | 14 | 58 | 2.5-384-7 |
| | | | 25 | 2950 | 28 | 58 | 4-384-7 |
| | 57 | 131 | 20 | 2950 | 21 | 60 | 4-384-7 |
| | | | 15 | 2950 | 15 | 60 | 2.5-384-7 |
| | 58 | 134 | 15 | 2950 | 15 | 61 | 2.5-384-7 |
| | 60 | 139 | 30 | 2950 | 32 | 63 | 4-384-7 |
| | 62 | 143 | 30 | 2950 | 32 | 65 | 4-384-7 |
| | 95 | 219 | 30 | 2950 | 31 | 100 | 2-384-11 |
| | 100 | 231 | 30 | 2950 | 33 | 105 | 2-384-11 |
| | 105 | 243 | 30 | 2950 | 35 | 110 | 2-384-11 |
| | 110 | 254 | 40 | 2950 | 37 | 115 | 2-384-11 |
| | 115 | 266 | 40 | 2950 | 39 | 120 | 2-384-11 |
| | 120 | 277 | 40 | 2950 | 41 | 125 | 2-384-11 |
| | | | 60 | 2950 | 67 | 123 | 3-384-13.5 |
| | | | 60 | 2950 | 67 | 123 | 3-384-13.5 |
| | 125 | 289 | 40 | 2950 | 43 | 130 | 2-384-11 |
| | | | 75 | 2950 | 70 | 128 | 3-384-13.5 |
| | 130 | 300 | 40 | 2950 | 45 | 135 | 2-384-11 |
| | | | 75 | 2950 | 74 | 134 | 3-384-13.5 |
| | 135 | 312 | 50 | 2950 | 47 | 140 | 2-384-11 |
| | | | 75 | 2950 | 77 | 139 | 3-384-13.5 |
| | 140 | 323 | 50 | 2950 | 49 | 145 | 2-384-11 |
| | | | 75 | 2950 | 81 | 143 | 3-384-13.5 |
| | 145 | 335 | 50 | 2950 | 51 | 150 | 2-384-11 |
| | | | 75 | 2950 | 84 | 148 | 3-384-13.5 |
| | 148 | 341 | 50 | 2950 | 51 | 153 | 2-384-11 |
| | 149 | 344 | 50 | 2950 | 52 | 155 | 2-384-11 |
| | 150 | 347 | 100 | 2950 | 88 | 153 | 3-384-13.5 |
| | 155 | 358 | 100 | 2950 | 92 | 158 | 3-384-13.5 |
| | 160 | 370 | 100 | 2950 | 95 | 163 | 3-384-13.5 |
| | 165 | 381 | 100 | 2950 | 99 | 168 | 3-384-13.5 |
| | 170 | 393 | 100 | 2950 | 103 | 173 | 3-384-13.5 |
| | 175 | 404 | 100 | 2950 | 107 | 178 | 3-384-13.5 |
| | 180 | 416 | 100 | 2950 | 110 | 183 | 3-384-13.5 |
| 185 | 427 | 100 | 2950 | 114 | 188 | 3-384-13.5 | |
| 190 | 439 | 125 | 2950 | 118 | 193 | 3-384-13.5 | |
| 195 | 450 | 125 | 2950 | 122 | 198 | 3-384-13.5 | |
| 200 | 462 | 125 | 2950 | 126 | 203 | 3-384-13.5 | |
| 205 | 474 | 125 | 2950 | 130 | 208 | 3-384-13.5 | |
| 210 | 485 | 125 | 2950 | 135 | 213 | 3-384-13.5 | |
| 215 | 497 | 125 | 2950 | 139 | 218 | 3-384-13.5 | |
| 216 | 499 | 125 | 2950 | 136 | 219 | 3-384-13.5 | |
| 218 | 504 | 125 | 2950 | 141 | 221 | 3-384-13.5 | |

*Maximum shutoff includes Hydraulic Institute's tolerance of 6%. Value is used to determine flange rating for the pump.



SELECTION TABLES
End Suction Fire Pumps
50Hz Electric Motor Driven

Section 911.5 Page 503
 Date November 15, 2018
 Supersedes January 1, 2018

| Flow | Pressure | | Required Motor HP Rating | | | Maximum Shutoff (PSI)* | Pump Model |
|----------------|----------|------|--------------------------|-------------|------------------|------------------------|------------|
| | | | Motor HP | Speed (RPM) | Horsepower (BHP) | | |
| | PSI | Feet | | | | | |
| 250 GPM | 44 | 102 | 20 | 2950 | 21 | 45 | 4-384-7 |
| | 45 | 104 | 20 | 2950 | 22 | 47 | 4-384-7 |
| | 50 | 116 | 25 | 2950 | 25 | 52 | 4-384-7 |
| | 55 | 127 | 25 | 2950 | 28 | 58 | 4-384-7 |
| | 56 | 130 | 20 | 2950 | 23 | 60 | 4-384-7 |
| | 60 | 139 | 30 | 2950 | 32 | 64 | 4-384-7 |
| | | | 40 | 2950 | 36 | 65 | 4-384-9.5 |
| | 62 | 143 | 30 | 2950 | 32 | 66 | 4-384-7 |
| | 65 | 150 | 40 | 2950 | 40 | 70 | 4-384-9.5 |
| | 70 | 162 | 40 | 2950 | 44 | 75 | 4-384-9.5 |
| | 75 | 173 | 50 | 2950 | 48 | 80 | 4-384-9.5 |
| | 76 | 176 | 30 | 2950 | 34 | 79 | 3-384-11 |
| | 80 | 185 | 40 | 2950 | 36 | 83 | 3-384-11 |
| | | | 50 | 2950 | 52 | 85 | 4-384-9.5 |
| | 85 | 196 | 40 | 2950 | 39 | 88 | 3-384-11 |
| | | | 50 | 2950 | 56 | 90 | 4-384-9.5 |
| | 90 | 208 | 40 | 2950 | 42 | 93 | 3-384-11 |
| | | | 60 | 2950 | 60 | 95 | 4-384-9.5 |
| | 91 | 210 | 30 | 2950 | 31 | 99 | 2-384-11 |
| | 95 | 219 | 30 | 2950 | 32 | 103 | 2-384-11 |
| | | | 40 | 2950 | 45 | 98 | 3-384-11 |
| | | | 60 | 2950 | 65 | 101 | 4-384-9.5 |
| | 100 | 231 | 30 | 2950 | 34 | 108 | 2-384-11 |
| | | | 50 | 2950 | 48 | 103 | 3-384-11 |
| | | | 60 | 2950 | 69 | 106 | 4-384-9.5 |
| | 105 | 243 | 40 | 2950 | 36 | 113 | 2-384-11 |
| | | | 50 | 2950 | 52 | 108 | 3-384-11 |
| | | | 75 | 2950 | 74 | 111 | 4-384-9.5 |
| | 110 | 254 | 40 | 2950 | 38 | 118 | 2-384-11 |
| | | | 50 | 2950 | 55 | 113 | 3-384-11 |
| | | | 75 | 2950 | 77 | 116 | 4-384-9.5 |
| | 111 | 256 | 75 | 2950 | 78 | 117 | 4-384-9.5 |
| | 115 | 266 | 40 | 2950 | 40 | 123 | 2-384-11 |
| | 119 | 275 | 60 | 2950 | 58 | 118 | 3-384-11 |
| | | | 60 | 2950 | 66 | 123 | 3-384-13.5 |
| | 120 | 277 | 40 | 2950 | 42 | 128 | 2-384-11 |
| | | | 60 | 2950 | 62 | 123 | 3-384-11 |
| | | | 60 | 2950 | 67 | 124 | 3-384-13.5 |
| | 125 | 289 | 40 | 2950 | 44 | 132 | 2-384-11 |
| | | | 60 | 2950 | 65 | 128 | 3-384-11 |
| | | | 75 | 2950 | 70 | 129 | 3-384-13.5 |
| | 130 | 300 | 40 | 2950 | 46 | 137 | 2-384-11 |
| | | | 60 | 2950 | 68 | 132 | 3-384-11 |
| | | | 75 | 2950 | 74 | 134 | 3-384-13.5 |
| | 135 | 312 | 50 | 2950 | 48 | 142 | 2-384-11 |
| | | | 75 | 2950 | 72 | 137 | 3-384-11 |
| | | | 75 | 2950 | 77 | 139 | 3-384-13.5 |
| | 140 | 323 | 50 | 2950 | 50 | 147 | 2-384-11 |
| 75 | | | 2950 | 76 | 142 | 3-384-11 | |
| 75 | | | 2950 | 81 | 144 | 3-384-13.5 | |
| 145 | 335 | 50 | 2950 | 51 | 152 | 2-384-11 | |
| | | 75 | 2950 | 79 | 147 | 3-384-11 | |
| | | 75 | 2950 | 85 | 149 | 3-384-13.5 | |
| 146 | 337 | 50 | 2950 | 51 | 153 | 2-384-11 | |
| 147 | 340 | 50 | 2950 | 51 | 154 | 2-384-11 | |
| | | 75 | 2950 | 79 | 150 | 3-384-11 | |
| 148 | 342 | 75 | 2950 | 79 | 150 | 3-384-11 | |

*Maximum shutoff includes Hydraulic Institute's tolerance of 6%. Value is used to determine flange rating for the pump.



**SELECTION TABLES
End Suction Fire Pumps
50Hz Electric Motor Driven**

Section 911.5 Page 504
Date November 15, 2018
Supersedes January 1, 2018

| Flow | Pressure | | Required Motor HP Rating | | | Maximum Shutoff (PSI)* | Pump Model |
|---|----------|------|--------------------------|-------------|------------------|------------------------|------------|
| | | | Motor HP | Speed (RPM) | Horsepower (BHP) | | |
| | PSI | Feet | | | | | |
| 2 5 0 G P M | 150 | 347 | 100 | 2950 | 88 | 154 | 3-384-13.5 |
| | 155 | 358 | 100 | 2950 | 92 | 159 | 3-384-13.5 |
| | 160 | 370 | 100 | 2950 | 95 | 163 | 3-384-13.5 |
| | 165 | 381 | 100 | 2950 | 99 | 168 | 3-384-13.5 |
| | 170 | 393 | 100 | 2950 | 103 | 173 | 3-384-13.5 |
| | 175 | 404 | 100 | 2950 | 107 | 178 | 3-384-13.5 |
| | 180 | 416 | 100 | 2950 | 111 | 183 | 3-384-13.5 |
| | 185 | 427 | 100 | 2950 | 115 | 188 | 3-384-13.5 |
| | 190 | 439 | 125 | 2950 | 118 | 193 | 3-384-13.5 |
| | 195 | 450 | 125 | 2950 | 122 | 198 | 3-384-13.5 |
| | 200 | 462 | 125 | 2950 | 126 | 203 | 3-384-13.5 |
| | 205 | 474 | 125 | 2950 | 131 | 208 | 3-384-13.5 |
| | 210 | 485 | 125 | 2950 | 135 | 213 | 3-384-13.5 |
| | 215 | 497 | 125 | 2950 | 139 | 218 | 3-384-13.5 |
| | 216 | 499 | 125 | 2950 | 136 | 219 | 3-384-13.5 |
| 218 | 504 | 125 | 2950 | 142 | 221 | 3-384-13.5 | |

*Maximum shutoff includes Hydraulic Institute's tolerance of 6%. Value is used to determine flange rating for the pump.



SELECTION TABLES
End Suction Fire Pumps
50Hz Electric Motor Driven

Section 911.5 Page 505
 Date November 15, 2018
 Supersedes January 1, 2018

| Flow | Pressure | | Required Motor HP Rating | | | Maximum Shutoff (PSI)* | Pump Model |
|---------|----------|------|--------------------------|-------------|------------------|------------------------|------------|
| | PSI | Feet | Motor HP | Speed (RPM) | Horsepower (BHP) | | |
| 300 GPM | 44 | 102 | 20 | 2950 | 21 | 46 | 4-384-7 |
| | 45 | 104 | 20 | 2950 | 22 | 47 | 4-384-7 |
| | 50 | 116 | 25 | 2950 | 25 | 53 | 4-384-7 |
| | 55 | 127 | 25 | 2950 | 29 | 58 | 4-384-7 |
| | 56 | 129 | 25 | 2950 | 24 | 60 | 4-384-7 |
| | 60 | 139 | 30 | 2950 | 32 | 64 | 4-384-7 |
| | | | 40 | 2950 | 36 | 65 | 4-384-9.5 |
| | 61 | 141 | 30 | 2950 | 32 | 65 | 4-384-7 |
| | 65 | 150 | 40 | 2950 | 40 | 71 | 4-384-9.5 |
| | 70 | 162 | 40 | 2950 | 44 | 76 | 4-384-9.5 |
| | 75 | 173 | 30 | 2950 | 34 | 79 | 3-384-11 |
| | | | 30 | 2950 | 34 | 79 | 3-384-11 |
| | | | 50 | 2950 | 48 | 81 | 4-384-9.5 |
| | 80 | 185 | 40 | 2950 | 37 | 84 | 3-384-11 |
| | | | 50 | 2950 | 52 | 86 | 4-384-9.5 |
| | 85 | 196 | 40 | 2950 | 40 | 90 | 3-384-11 |
| | | | 50 | 2950 | 57 | 91 | 4-384-9.5 |
| | 87 | 201 | 30 | 2950 | 31 | 100 | 2-384-11 |
| | 90 | 208 | 30 | 2950 | 32 | 103 | 2-384-11 |
| | | | 40 | 2950 | 43 | 95 | 3-384-11 |
| | | | 60 | 2950 | 61 | 96 | 4-384-9.5 |
| | 95 | 219 | 30 | 2950 | 34 | 108 | 2-384-11 |
| | | | 40 | 2950 | 46 | 99 | 3-384-11 |
| | | | 60 | 2950 | 65 | 101 | 4-384-9.5 |
| | 100 | 231 | 40 | 2950 | 36 | 112 | 2-384-11 |
| | | | 50 | 2950 | 49 | 104 | 3-384-11 |
| | | | 75 | 2950 | 70 | 106 | 4-384-9.5 |
| | 105 | 243 | 40 | 2950 | 37 | 117 | 2-384-11 |
| | | | 50 | 2950 | 52 | 109 | 3-384-11 |
| | | | 75 | 2950 | 75 | 111 | 4-384-9.5 |
| | 110 | 254 | 75 | 2950 | 77 | 116 | 4-384-9.5 |
| | | | 40 | 2950 | 39 | 122 | 2-384-11 |
| | | | 50 | 2950 | 55 | 114 | 3-384-11 |
| | | | 75 | 2950 | 77 | 116 | 4-384-9.5 |
| | 111 | 256 | 75 | 2950 | 79 | 117 | 4-384-9.5 |
| | 115 | 266 | 40 | 2950 | 41 | 126 | 2-384-11 |
| | | | 60 | 2950 | 59 | 118 | 3-384-11 |
| | 119 | 275 | 60 | 2950 | 67 | 123 | 3-384-13.5 |
| | 120 | 277 | 40 | 2950 | 43 | 131 | 2-384-11 |
| | | | 60 | 2950 | 62 | 123 | 3-384-11 |
| | | | 60 | 2950 | 67 | 124 | 3-384-13.5 |
| | 125 | 289 | 40 | 2950 | 45 | 135 | 2-384-11 |
| | | | 60 | 2950 | 65 | 128 | 3-384-11 |
| | | | 75 | 2950 | 71 | 129 | 3-384-13.5 |
| 130 | 300 | 50 | 2950 | 47 | 140 | 2-384-11 | |
| | | 60 | 2950 | 69 | 133 | 3-384-11 | |
| | | 75 | 2950 | 74 | 135 | 3-384-13.5 | |
| 135 | 312 | 50 | 2950 | 49 | 145 | 2-384-11 | |
| | | 75 | 2950 | 72 | 138 | 3-384-11 | |
| | | 75 | 2950 | 78 | 140 | 3-384-13.5 | |
| 140 | 323 | 50 | 2950 | 51 | 149 | 2-384-11 | |
| | | 75 | 2950 | 76 | 143 | 3-384-11 | |
| | | 75 | 2950 | 81 | 144 | 3-384-13.5 | |

*Maximum shutoff includes Hydraulic Institute's tolerance of 6%. Value is used to determine flange rating for the pump.



**SELECTION TABLES
End Suction Fire Pumps
50Hz Electric Motor Driven**

Section 911.5 Page 506
Date November 15, 2018
Supersedes January 1, 2018

| Flow | Pressure | | Required Motor HP Rating | | | Maximum Shutoff (PSI)* | Pump Model |
|---|----------|------|--------------------------|-------------|------------------|------------------------|------------|
| | PSI | Feet | Motor HP | Speed (RPM) | Horsepower (BHP) | | |
| 3 0 0 G P M | 145 | 335 | 50 | 2950 | 51 | 155 | 2-384-11 |
| | | | 75 | 2950 | 78 | 148 | 3-384-11 |
| | | | 75 | 2950 | 85 | 149 | 3-384-13.5 |
| | 147 | 339 | 75 | 2950 | 79 | 150 | 3-384-11 |
| | | | 75 | 2950 | 79 | 150 | 3-384-11 |
| | 150 | 347 | 100 | 2950 | 88 | 154 | 3-384-13.5 |
| | 155 | 358 | 100 | 2950 | 92 | 159 | 3-384-13.5 |
| | 160 | 370 | 100 | 2950 | 96 | 164 | 3-384-13.5 |
| | 165 | 381 | 100 | 2950 | 100 | 169 | 3-384-13.5 |
| | 170 | 393 | 100 | 2950 | 103 | 174 | 3-384-13.5 |
| | 175 | 404 | 100 | 2950 | 107 | 179 | 3-384-13.5 |
| | 180 | 416 | 100 | 2950 | 111 | 184 | 3-384-13.5 |
| | 185 | 427 | 100 | 2950 | 115 | 188 | 3-384-13.5 |
| | 190 | 439 | 125 | 2950 | 119 | 193 | 3-384-13.5 |
| | 195 | 450 | 125 | 2950 | 123 | 198 | 3-384-13.5 |
| | 200 | 462 | 125 | 2950 | 127 | 203 | 3-384-13.5 |
| | 205 | 474 | 125 | 2950 | 131 | 208 | 3-384-13.5 |
| | 210 | 485 | 125 | 2950 | 135 | 213 | 3-384-13.5 |
| 215 | 497 | 125 | 2950 | 139 | 218 | 3-384-13.5 | |
| 216 | 498 | 125 | 2950 | 136 | 219 | 3-384-13.5 | |
| 218 | 504 | 125 | 2950 | 142 | 221 | 3-384-13.5 | |

*Maximum shutoff includes Hydraulic Institute's tolerance of 6%. Value is used to determine flange rating for the pump.



SELECTION TABLES
End Suction Fire Pumps
50Hz Electric Motor Driven

Section 911.5 Page 507
 Date November 15, 2018
 Supersedes January 1, 2018

| Flow | Pressure | | Required Motor HP Rating | | | Maximum Shutoff (PSI)* | Pump Model |
|----------------|----------|------|--------------------------|-------------|------------------|------------------------|------------|
| | | | Motor HP | Speed (RPM) | Horsepower (BHP) | | |
| | PSI | Feet | | | | | |
| 400 GPM | 42 | 97 | 20 | 2950 | 21 | 45 | 4-384-7 |
| | 45 | 104 | 20 | 2950 | 23 | 48 | 4-384-7 |
| | 50 | 116 | 25 | 2950 | 26 | 54 | 4-384-7 |
| | 55 | 127 | 30 | 2950 | 30 | 60 | 4-384-7 |
| | 59 | 136 | 40 | 2950 | 36 | 66 | 4-384-9.5 |
| | 60 | 139 | 30 | 2950 | 32 | 65 | 4-384-7 |
| | | | 40 | 2950 | 37 | 67 | 4-384-9.5 |
| | 61 | 141 | 30 | 2950 | 31 | 66 | 4-384-7 |
| | 65 | 150 | 40 | 2950 | 41 | 72 | 4-384-9.5 |
| | 70 | 162 | 40 | 2950 | 45 | 77 | 4-384-9.5 |
| | 72 | 166 | 30 | 2950 | 34 | 79 | 3-384-11 |
| | 75 | 173 | 40 | 2950 | 36 | 82 | 3-384-11 |
| | | | 50 | 2950 | 49 | 82 | 4-384-9.5 |
| | 80 | 185 | 40 | 2950 | 39 | 88 | 3-384-11 |
| | | | 50 | 2950 | 53 | 87 | 4-384-9.5 |
| | 85 | 196 | 40 | 2950 | 42 | 93 | 3-384-11 |
| | | | 50 | 2950 | 58 | 92 | 4-384-9.5 |
| | 90 | 208 | 40 | 2950 | 45 | 97 | 3-384-11 |
| | | | 60 | 2950 | 62 | 97 | 4-384-9.5 |
| | 95 | 219 | 50 | 2950 | 48 | 102 | 3-384-11 |
| | | | 60 | 2950 | 66 | 102 | 4-384-9.5 |
| | 100 | 231 | 50 | 2950 | 51 | 106 | 3-384-11 |
| | | | 75 | 2950 | 71 | 107 | 4-384-9.5 |
| | 105 | 243 | 50 | 2950 | 54 | 111 | 3-384-11 |
| | | | 75 | 2950 | 76 | 112 | 4-384-9.5 |
| | 109 | 251 | 75 | 2950 | 77 | 116 | 4-384-9.5 |
| | | | 75 | 2950 | 77 | 116 | 4-384-9.5 |
| | 110 | 254 | 50 | 2950 | 57 | 116 | 3-384-11 |
| | 115 | 266 | 60 | 2950 | 60 | 120 | 3-384-11 |
| | 118 | 273 | 60 | 2950 | 67 | 124 | 3-384-13.5 |
| | 120 | 277 | 60 | 2950 | 63 | 125 | 3-384-11 |
| | | | 60 | 2950 | 68 | 126 | 3-384-13.5 |
| | 125 | 289 | 60 | 2950 | 67 | 130 | 3-384-11 |
| | | | 75 | 2950 | 72 | 131 | 3-384-13.5 |
| | 130 | 300 | 75 | 2950 | 70 | 134 | 3-384-11 |
| | | | 75 | 2950 | 75 | 136 | 3-384-13.5 |
| | 135 | 312 | 75 | 2950 | 74 | 139 | 3-384-11 |
| | | | 75 | 2950 | 79 | 141 | 3-384-13.5 |
| | 140 | 323 | 75 | 2950 | 77 | 144 | 3-384-11 |
| | | | 75 | 2950 | 82 | 145 | 3-384-13.5 |
| | 145 | 335 | 75 | 2950 | 79 | 149 | 3-384-11 |
| | | | 75 | 2950 | 86 | 150 | 3-384-13.5 |
| 75 | | | 2950 | 79 | 150 | 3-384-11 | |
| 146 | 337 | 75 | 2950 | 79 | 150 | 3-384-11 | |
| 150 | 347 | 100 | 2950 | 89 | 155 | 3-384-13.5 | |
| 155 | 358 | 100 | 2950 | 93 | 160 | 3-384-13.5 | |
| 160 | 370 | 100 | 2950 | 97 | 165 | 3-384-13.5 | |
| 165 | 381 | 100 | 2950 | 100 | 170 | 3-384-13.5 | |
| 170 | 393 | 100 | 2950 | 104 | 175 | 3-384-13.5 | |
| 175 | 404 | 100 | 2950 | 108 | 180 | 3-384-13.5 | |
| 180 | 416 | 100 | 2950 | 112 | 185 | 3-384-13.5 | |
| 185 | 427 | 125 | 2950 | 116 | 189 | 3-384-13.5 | |
| 190 | 439 | 125 | 2950 | 120 | 194 | 3-384-13.5 | |
| 195 | 450 | 125 | 2950 | 124 | 199 | 3-384-13.5 | |
| 200 | 462 | 125 | 2950 | 128 | 204 | 3-384-13.5 | |
| 205 | 474 | 125 | 2950 | 132 | 209 | 3-384-13.5 | |
| 210 | 485 | 125 | 2950 | 136 | 214 | 3-384-13.5 | |
| 215 | 496 | 125 | 2950 | 136 | 219 | 3-384-13.5 | |
| 215 | 497 | 125 | 2950 | 140 | 219 | 3-384-13.5 | |
| 216 | 499 | 125 | 2950 | 141 | 220 | 3-384-13.5 | |

*Maximum shutoff includes Hydraulic Institute's tolerance of 6%. Value is used to determine flange rating for the pump.



SELECTION TABLES
End Suction Fire Pumps
50Hz Electric Motor Driven

Section 911.5 Page 508
 Date November 15, 2018
 Supersedes January 1, 2018

| Flow | Pressure | | Required Motor HP Rating | | | Maximum Shutoff (PSI)* | Pump Model |
|---------|----------|------|--------------------------|-------------|------------------|------------------------|------------|
| | PSI | Feet | Motor HP | Speed (RPM) | Horsepower (BHP) | | |
| 450 GPM | 42 | 97 | 20 | 2950 | 21 | 46 | 4-384-7 |
| | 45 | 104 | 20 | 2950 | 23 | 49 | 4-384-7 |
| | 50 | 116 | 25 | 2950 | 26 | 55 | 4-384-7 |
| | 54 | 125 | 25 | 2950 | 28 | 59 | 4-384-7 |
| | 55 | 127 | 30 | 2950 | 30 | 60 | 4-384-7 |
| | 58 | 134 | 40 | 2950 | 36 | 65 | 4-384-9.5 |
| | 60 | 139 | 30 | 2950 | 32 | 66 | 4-384-7 |
| | | | 40 | 2950 | 38 | 67 | 4-384-9.5 |
| | 65 | 150 | 40 | 2950 | 41 | 73 | 4-384-9.5 |
| | 70 | 162 | 30 | 2950 | 34 | 79 | 3-384-11 |
| | | | 40 | 2950 | 45 | 77 | 4-384-9.5 |
| | 75 | 173 | 40 | 2950 | 37 | 85 | 3-384-11 |
| | | | 50 | 2950 | 50 | 83 | 4-384-9.5 |
| | 80 | 185 | 40 | 2950 | 40 | 90 | 3-384-11 |
| | | | 50 | 2950 | 54 | 88 | 4-384-9.5 |
| | 85 | 196 | 40 | 2950 | 43 | 96 | 3-384-11 |
| | | | 60 | 2950 | 58 | 93 | 4-384-9.5 |
| | 90 | 208 | 40 | 2950 | 46 | 99 | 3-384-11 |
| | | | 60 | 2950 | 62 | 98 | 4-384-9.5 |
| | 95 | 219 | 50 | 2950 | 49 | 103 | 3-384-11 |
| | | | 60 | 2950 | 67 | 103 | 4-384-9.5 |
| | 100 | 231 | 50 | 2950 | 52 | 108 | 3-384-11 |
| | | | 75 | 2950 | 72 | 108 | 4-384-9.5 |
| | 105 | 243 | 50 | 2950 | 55 | 112 | 3-384-11 |
| | | | 75 | 2950 | 76 | 113 | 4-384-9.5 |
| | 108 | 250 | 75 | 2950 | 77 | 116 | 4-384-9.5 |
| | 109 | 252 | 75 | 2950 | 77 | 117 | 4-384-9.5 |
| | 110 | 254 | 50 | 2950 | 58 | 117 | 3-384-11 |
| | 115 | 266 | 60 | 2950 | 61 | 122 | 3-384-11 |
| | 117 | 270 | 60 | 2950 | 67 | 124 | 3-384-13.5 |
| | 120 | 277 | 60 | 2950 | 64 | 126 | 3-384-11 |
| | | | 60 | 2950 | 69 | 127 | 3-384-13.5 |
| | 125 | 289 | 60 | 2950 | 68 | 131 | 3-384-11 |
| | | | 75 | 2950 | 72 | 132 | 3-384-13.5 |
| | 130 | 300 | 75 | 2950 | 71 | 135 | 3-384-11 |
| | | | 75 | 2950 | 76 | 137 | 3-384-13.5 |
| | 135 | 312 | 75 | 2950 | 74 | 140 | 3-384-11 |
| | | | 75 | 2950 | 79 | 142 | 3-384-13.5 |
| | 140 | 323 | 75 | 2950 | 78 | 145 | 3-384-11 |
| | | | 75 | 2950 | 83 | 146 | 3-384-13.5 |
| | 144 | 333 | 75 | 2950 | 79 | 150 | 3-384-11 |
| | 145 | 335 | 75 | 2950 | 79 | 150 | 3-384-11 |
| 75 | | | 2950 | 86 | 151 | 3-384-13.5 | |
| 146 | 337 | 75 | 2950 | 80 | 151 | 3-384-11 | |
| 150 | 347 | 100 | 2950 | 90 | 156 | 3-384-13.5 | |
| 155 | 358 | 100 | 2950 | 94 | 161 | 3-384-13.5 | |
| 160 | 370 | 100 | 2950 | 97 | 166 | 3-384-13.5 | |
| 165 | 381 | 100 | 2950 | 101 | 171 | 3-384-13.5 | |
| 170 | 393 | 100 | 2950 | 105 | 176 | 3-384-13.5 | |
| 175 | 404 | 100 | 2950 | 109 | 180 | 3-384-13.5 | |
| 180 | 416 | 100 | 2950 | 112 | 185 | 3-384-13.5 | |
| 185 | 427 | 125 | 2950 | 116 | 190 | 3-384-13.5 | |
| 190 | 439 | 125 | 2950 | 120 | 195 | 3-384-13.5 | |
| 195 | 450 | 125 | 2950 | 124 | 199 | 3-384-13.5 | |
| 200 | 462 | 125 | 2950 | 128 | 205 | 3-384-13.5 | |
| 205 | 474 | 125 | 2950 | 132 | 210 | 3-384-13.5 | |
| 210 | 485 | 125 | 2950 | 136 | 215 | 3-384-13.5 | |
| 214 | 494 | 125 | 2950 | 136 | 219 | 3-384-13.5 | |
| 215 | 497 | 125 | 2950 | 140 | 220 | 3-384-13.5 | |

*Maximum shutoff includes Hydraulic Institute's tolerance of 6%. Value is used to determine flange rating for the pump.



SELECTION TABLES
End Suction Fire Pumps
50Hz Electric Motor Driven

Section 911.5 Page 509
 Date November 15, 2018
 Supersedes January 1, 2018

| Flow | Pressure | | Required Motor HP Rating | | | Maximum Shutoff (PSI)* | Pump Model |
|----------------|----------|------|--------------------------|-------------|------------------|------------------------|------------|
| | PSI | Feet | Motor HP | Speed (RPM) | Horsepower (BHP) | | |
| 500 GPM | 41 | 95 | 20 | 2950 | 21 | 46 | 4-384-7 |
| | 45 | 104 | 25 | 2950 | 24 | 50 | 4-384-7 |
| | 50 | 116 | 25 | 2950 | 27 | 56 | 4-384-7 |
| | 54 | 124 | 25 | 2950 | 29 | 59 | 4-384-7 |
| | 55 | 127 | 30 | 2950 | 30 | 61 | 4-384-7 |
| | 57 | 132 | 40 | 2950 | 36 | 66 | 4-384-9.5 |
| | 60 | 139 | 30 | 2950 | 32 | 66 | 4-384-7 |
| | | | 40 | 2950 | 38 | 69 | 4-384-9.5 |
| | 65 | 150 | 40 | 2950 | 42 | 75 | 4-384-9.5 |
| | 68 | 157 | 30 | 2950 | 34 | 79 | 3-384-11 |
| | 70 | 162 | 40 | 2950 | 35 | 82 | 3-384-11 |
| | | | 40 | 2950 | 46 | 79 | 4-384-9.5 |
| | 75 | 173 | 40 | 2950 | 38 | 87 | 3-384-11 |
| | | | 50 | 2950 | 50 | 84 | 4-384-9.5 |
| | 80 | 185 | 40 | 2950 | 41 | 93 | 3-384-11 |
| | | | 50 | 2950 | 54 | 89 | 4-384-9.5 |
| | 85 | 196 | 40 | 2950 | 44 | 99 | 3-384-11 |
| | | | 60 | 2950 | 59 | 94 | 4-384-9.5 |
| | 90 | 208 | 50 | 2950 | 47 | 100 | 3-384-11 |
| | | | 60 | 2950 | 63 | 99 | 4-384-9.5 |
| | 95 | 219 | 50 | 2950 | 50 | 105 | 3-384-11 |
| | | | 60 | 2950 | 68 | 104 | 4-384-9.5 |
| | 100 | 231 | 50 | 2950 | 53 | 110 | 3-384-11 |
| | | | 75 | 2950 | 72 | 109 | 4-384-9.5 |
| | 105 | 243 | 50 | 2950 | 56 | 114 | 3-384-11 |
| | | | 75 | 2950 | 77 | 115 | 4-384-9.5 |
| | 108 | 248 | 75 | 2950 | 77 | 117 | 4-384-9.5 |
| | | | 75 | 2950 | 77 | 118 | 4-384-9.5 |
| | 110 | 254 | 60 | 2950 | 59 | 119 | 3-384-11 |
| | 115 | 266 | 60 | 2950 | 62 | 123 | 3-384-11 |
| | | | 60 | 2950 | 66 | 123 | 3-384-13.5 |
| | 120 | 277 | 60 | 2950 | 65 | 128 | 3-384-11 |
| | | | 75 | 2950 | 70 | 128 | 3-384-13.5 |
| | 125 | 289 | 60 | 2950 | 69 | 132 | 3-384-11 |
| | | | 75 | 2950 | 73 | 133 | 3-384-13.5 |
| | 130 | 300 | 75 | 2950 | 72 | 136 | 3-384-11 |
| | | | 75 | 2950 | 77 | 138 | 3-384-13.5 |
| | 135 | 312 | 75 | 2950 | 75 | 141 | 3-384-11 |
| | | | 75 | 2950 | 80 | 144 | 3-384-13.5 |
| | 140 | 323 | 75 | 2950 | 79 | 147 | 3-384-11 |
| | | | 75 | 2950 | 84 | 147 | 3-384-13.5 |
| | 143 | 330 | 75 | 2950 | 79 | 150 | 3-384-11 |
| 144 | 333 | 75 | 2950 | 79 | 151 | 3-384-11 | |
| 145 | 335 | 100 | 2950 | 87 | 152 | 3-384-13.5 | |
| 150 | 347 | 100 | 2950 | 91 | 157 | 3-384-13.5 | |
| 155 | 358 | 100 | 2950 | 94 | 162 | 3-384-13.5 | |
| 160 | 370 | 100 | 2950 | 98 | 167 | 3-384-13.5 | |
| 165 | 381 | 100 | 2950 | 102 | 172 | 3-384-13.5 | |
| 170 | 393 | 100 | 2950 | 106 | 177 | 3-384-13.5 | |
| 175 | 404 | 100 | 2950 | 109 | 181 | 3-384-13.5 | |
| 180 | 416 | 100 | 2950 | 113 | 186 | 3-384-13.5 | |
| 185 | 427 | 125 | 2950 | 117 | 191 | 3-384-13.5 | |
| 190 | 439 | 125 | 2950 | 121 | 196 | 3-384-13.5 | |
| 195 | 450 | 125 | 2950 | 125 | 200 | 3-384-13.5 | |
| 200 | 462 | 125 | 2950 | 129 | 205 | 3-384-13.5 | |
| 205 | 474 | 125 | 2950 | 133 | 211 | 3-384-13.5 | |
| 210 | 485 | 125 | 2950 | 137 | 216 | 3-384-13.5 | |
| 215 | 497 | 125 | 2950 | 141 | 221 | 3-384-13.5 | |

*Maximum shutoff includes Hydraulic Institute's tolerance of 6%. Value is used to determine flange rating for the pump.



**SELECTION TABLES
End Suction Fire Pumps
50Hz Electric Motor Driven**

Section 911.5 Page 510
Date November 15, 2018
Supersedes January 1, 2018

| Flow | Pressure | | Required Motor HP Rating | | | Maximum Shutoff (PSI)* | Pump Model |
|---|----------|------|--------------------------|-------------|------------------|------------------------|------------|
| | PSI | Feet | Motor HP | Speed (RPM) | Horsepower (BHP) | | |
| 7 5 0 G P M | 52 | 120 | 40 | 2950 | 36 | 65 | 4-384-9.5 |
| | 55 | 127 | 40 | 2950 | 38 | 68 | 4-384-9.5 |
| | 60 | 139 | 40 | 2950 | 42 | 74 | 4-384-9.5 |
| | 65 | 150 | 40 | 2950 | 46 | 78 | 4-384-9.5 |
| | 70 | 162 | 50 | 2950 | 50 | 83 | 4-384-9.5 |
| | 75 | 173 | 50 | 2950 | 54 | 88 | 4-384-9.5 |
| | 80 | 185 | 60 | 2950 | 58 | 93 | 4-384-9.5 |
| | 85 | 196 | 60 | 2950 | 63 | 98 | 4-384-9.5 |
| | 90 | 208 | 60 | 2950 | 67 | 103 | 4-384-9.5 |
| | 95 | 219 | 75 | 2950 | 72 | 107 | 4-384-9.5 |
| | 100 | 231 | 75 | 2950 | 76 | 113 | 4-384-9.5 |
| | 104 | 240 | 75 | 2950 | 77 | 117 | 4-384-9.5 |

*Maximum shutoff includes Hydraulic Institute's tolerance of 6%. Value is used to determine flange rating for the pump.

